

Ghost



A recessed profile for ground installation, particularly durable and reliable, **ideal for use in drive-over areas**. The AISI 316 stainless steel casing ensures resistance to adverse climatic conditions and makes it suitable for high salinity environments.

Passive heat dissipation


AISI 316 stainless steel casing for high salinity environments

Light management

Four optics available ensuring maximum design flexibility, protected by 19 mm thick toughened glass




Ghost RGB | Linear profiles | powerLED 18 W 24 V



type	colour	optic
Steel	88872	RGB
		Z
		20°
		50°
		Asym.
		20
		50
		07

99076	99278	89284	89282	89362
IR Remote	DMX	Outer casing	Outer casing	5 m cable


Ghost RGB | Linear profiles | topLED 5 W 24 V



type	colour	optic
Steel	88876	RGB
		Z
		Diff.
		00

99076	99278	89282	89284	89362
IR Remote	DMX	Outer casing	Outer casing	5 m cable


Ghost RGB | Linear profiles | powerLED 27 W 24 V



type	colour	optic
Steel	88873	RGB
		Z
		20°
		50°
		Asym.
		20
		50
		07

99076	99278	89285	89283	89362
IR Remote	DMX	Outer casing	Outer casing	5 m cable

Ghost RGB | Linear profiles | topLED 7 W 24 V



type	colour	optic
Steel	88877	RGB
		Z
		Diff.
		00


99076	99278	89283	89285	89362
IR Remote	DMX	Outer casing	Outer casing	5 m cable

Ghost | Walk-over outer-casing



type	L. mm	suitable for	
Steel	486	88870 - 88872 - 88874 - 88876	89284
Steel	736	88871 - 88873 - 88875 - 88877	89285

Ghost | Drive-over outer-casing



type	L. mm	suitable for	
Steel	486	88870 - 88872 - 88874 - 88876	89282
Steel	736	88871 - 88873 - 88875 - 88877	89283

Cables | Power 24V DC



connectors	sec. Ø	suitable for	L. m
F 4 pin M12	4 x 0,5 mm ²	Ghost	1,5 99216
			5 89190

Extension cable | Power 24V DC



connectors	sec. Ø	suitable for	L. m
M + F 4 pin M12	4 x 0,5 mm ²	Ghost	1 98437
			5 98149
			10 89188

Cables | Power RGB 24V DC



connectors	sec. Ø	suitable for	L. m
M 5 pin M12	5 x 0,5 mm ²	Ghost RGB	5 89362

Extension cable | Power RGB 24V DC



connectors	sec. Ø	suitable for	L. m
M + F 5 pin M12	5 x 0,5 mm ²	Ghost RGB	10 89361

