

## VEDO DP SINGLE

Mastauslegerleuchte

10.08600.4500 1XLED 40W SKI oder SK II (3000K oder 4000K)

Pole mounted luminaire with bracket VEDO DP 4500 single

Luminaire and roof made of aluminium

Roof 760 x 760 mm with facets for place illumination

Reflector of special-purpose plastic with individual facets

Vaporised surface with double protection coating

For asymmetric, indirect illumination

Elec. equip.: 1x HP LED

Power consumption approx. 40W

Reflector LED: 10°

==> Colour temperature: warm white (3000 K) or neutral white (4000 K)

(to be specified)

==> Protection rating I or II

(to be specified)

Ingress protection IP65

Tapered pole made of steel, galvanized

(Pole ø bottom 140 mm / pole ø top 76 mm)

LSH 4500 mm

Embedded base 900 mm with 2 openings for cable entry

With inspection-door and C-rail for fuse-box

With second inspection-door below the luminaire

(For electrical equipment)

Colour: RAL (classic-unicolour)/HESS-DB+Glimmer - RAL

Pearl-Metallic - only on request (to be specified)



### Advantages

- Brilliant optical light control and efficiency thanks to high-quality secondary reflector
- Almost glare-free lighting, even for high illumination levels

### Downloads

**VEDO DP SINGLE**