aspho

A perfect example of distributed lighting: Aspho is efficient, practical and comes with very discrete dimensions. It offers a wide range of available colour temperatures. It can be installed on plasterboards, using recessed casings.

Materials
Brass or steel body

Fox Belysning AB Tellusgången 8 Telefonplan 126 26 Hägersten 08-440 85 40

Aspho_R | Decorative spotlight | 24 V | 5mmLED 0,5 W

C.V. IP44

15

White	**88417**	3000 K	**W**	Medium Flood	**30**
Chrome	**85001**	5000 K	**C**		
Nickel	**85002**				

Electronics

99374	**99332**	**99722**
ON/OFF	0/1-10V	DALI
1 - 150 art.	1 - 300 art.	1 - 240 art.

1009 Recessed casing

84916 / 84335

RTG **88417W30**
88417C00
85001W30
85001C30
85002W30

Aspho_R | Decorative spotlight | powerLED 1 W 350 mA

C.C. IP44

15

White	**91340**	2700 K	98 lm	**M**	Flood	**70**
Chrome	**85025**	3000 K	107 lm	**W**		
Nickel	**85026**	4000 K	114 lm	**N**		
		5000 K	139 lm	**C**		
White	**88418**	2700 K	98 lm	**M**	Wide Flood	**12**
Chrome	**85013**	3000 K	107 lm	**W**		
Nickel	**85014**	4000 K	114 lm	**N**		
		5000 K	139 lm	**C**		

Electronics

89144	**99708**	+ driver CV 24V	**99711**	+ driver CV 24V
ON/OFF	0/1-10V converter	981	DALI converter	981
1 - 2 art.	1 - 4 art.		1 - 4 art.	

1009 Recessed casing

84916 / 84335

RTG **91340W70** **85026W70**
91340C70 **85026N70**
85025W70 **88418W12**
85025N70 **85013W12**
85025C70 **85014W12**

Aspho_R | Decorative spotlight | powerLED 1,5 W 500 mA

C.C. IP44

15

White	**91344**	2700 K	130 lm	**M**	Flood	**70**
Chrome	**85959**	3000 K	143 lm	**W**		
Nickel	**85960**	4000 K	152 lm	**N**		
		5000 K	185 lm	**C**		
White	**91346**	2700 K	130 lm	**M**	Wide Flood	**12**
Chrome	**85947**	3000 K	143 lm	**W**		
Nickel	**85948**	4000 K	152 lm	**N**		
		5000 K	185 lm	**C**		

Electronics

99195	**99709**	+ driver CV 24V	**99712**	+ driver CV 24V
ON/OFF	0/1-10V converter	981	DALI converter	981
1 - 2 art.	1 art.		1 art.	

1009 Recessed casing

84917

RTG **91344W70**
85960W70

Aspho_R | Decorative spotlight | 24 V | 5mmLED 1.5 W

C.V. IP44

15

White	91352	RGB	Z	Flood	30
Chrome	86707				
Nickel	86708				

Electronics

RF driver CV
985

DMX driver CV
985

DMX controllers
995

driver CV 24V
981-982

switching CV 24V
986-989

1009 Recessed casing
84916

RTG **91352Z30**
86708Z30

Aspho_R | Decorative spotlight | powerLED 2,1 W 220 mA

C.C. IP44

15

White	91354	RGB	Z	Flood	70
Chrome	86730				
Nickel	86731				
White	91362	RGB	Z	Wide Flood	12
Chrome	87214				
Nickel	87215				

Electronics

RF driver CC
972

DMX driver CC
977

DMX controllers
995

driver CV 24V/48V
981-982

switching CV 24V/48V
986-989

1009 Recessed casing
84917

Aspho_Q | Decorative spotlight | 24 V | 5mmLED 0,5 W

C.V. IP44

15

White	**91339**	3000 K	**W**	Medium Flood	**30**
Chrome	**85004**	5000 K	**C**		
Nickel	**85005**				

Electronics

99374	**99332**	**99722**
ON/OFF	0/1-10V	DALI
1 - 150 art.	1 - 300 art.	1 - 240 art.

1009 Recessed casing
84916 / 84335

Aspho_Q | Decorative spotlight | powerLED 1 W 350 mA

C.C. IP44

15

White	**91341**	2700 K	98 lm	**M**	Flood	**70**
Chrome	**85028**	3000 K	107 lm	**W**		
Nickel	**85029**	4000 K	114 lm	**N**		
		5000 K	139 lm	**C**		
White	**91343**	3000 K	98 lm	**W**	Wide Flood	**12**
Chrome	**85016**	4000 K	114 lm	**N**		
Nickel	**85017**	5000 K	139 lm	**C**		

1009 Recessed casing
84916 / 84335

RTG **91341W70**

Electronics

89144	**99708**	**99711**
ON/OFF	0/1-10V converter	DALI converter
1 - 2 art.	1 - 4 art.	1 - 4 art.
	+ driver CV 24V	+ driver CV 24V
	981	981

Aspho_Q | Decorative spotlight | powerLED 1,5 W 500 mA

C.C. IP44

15

White	**91345**	2700 K	130 lm	**M**	Flood	**70**
Chrome	**85962**	3000 K	143 lm	**W**		
Nickel	**85963**	4000 K	152 lm	**N**		
		5000 K	185 lm	**C**		
White	**91347**	2700 K	130 lm	**M**	Wide Flood	**12**
Chrome	**85950**	3000 K	143 lm	**W**		
Nickel	**85951**	4000 K	152 lm	**N**		
		5000 K	185 lm	**C**		

1009 Recessed casing
84917

Electronics

99195	**99709**	**99712**
ON/OFF	0/1-10V converter	DALI converter
1 - 2 art.	1 art.	1 art.
	+ driver CV 24V	+ driver CV 24V
	981	981