

# bibok





With a flange measuring just 9 mm, Bibok allows to obtain captivating lighting effects without affecting the architecture. With its ultra-minimalist design, fit for plasterboard-installation thanks to the recessed casing, this recessed spotlight enhances spaces with refined bright spots.

#### **Materials**

Brass body

**Bibok | Decorative spotlight | 24 V | 5mmLED 0,5 W**



White	<b>91366</b>	3000 K	<b>W</b>	Medium Flood	<b>30</b>
Nickel	<b>85335</b>	5000 K	<b>C</b>		

**Electronics**

 <b>99374</b> ON/OFF 1 - 150 art.	 <b>99332</b> 0/1-10V 1 - 300 art.	 <b>99722</b> DALI 1 - 240 art.
--	---	--

- RTG **91366W30**
- 91366C30**
- 85335W30**
- 85335C30**

**Bibok | Decorative spotlight | powerLED 1 W 350 mA**



White	<b>91348</b>	3000 K	107 lm	<b>W</b>	Flood	<b>70</b>
Chrome	<b>85976</b>	4000 K	114 lm	<b>N</b>		
		5000 K	139 lm	<b>C</b>		

White	<b>91350</b>	3000 K	107 lm	<b>W</b>	Wide Flood	<b>12</b>
Chrome	<b>85575</b>	4000 K	114 lm	<b>N</b>		
		5000 K	139 lm	<b>C</b>		


**Electronics**

 <b>89144</b> ON/OFF 1 - 2 art.	 <b>99708</b> 0/1-10V converter 1 - 4 art.	+ driver CV 24V 	 <b>99711</b> DALI converter 1 - 4 art.	+ driver CV 24V 
--	---	---------------------	--	---------------------

- RTG **85575W12**
- 91348W70**
- 85976W70**

▶ 1009 Recessed casing  
**84916**

**Bibok | Decorative spotlight | powerLED 1.5 W 500 mA**



White	<b>91349</b>	3000 K	143 lm	<b>W</b>	Flood	<b>70</b>
Chrome	<b>85979</b>	4000 K	152 lm	<b>N</b>		
		5000 K	185 lm	<b>C</b>		

**Electronics**

 <b>99195</b> ON/OFF 1 - 2 art.	 <b>99709</b> 0/1-10V converter 1 art.	+ driver CV 24V 	 <b>99712</b> DALI converter 1 art.	+ driver CV 24V 
--	---	---------------------	--	---------------------

▶ 1009 Recessed casing  
**84917**