

Calypto



Directional spotlight with joint for recessed mounting. Installation with screws or with recessed mounting on plasterboard using springs or outer casing. **Designed to enhance the displayed object in recesses or cases.**


Passive heat dissipation

Brass casing with chrome or nickel finish

Practical installation

Surface mounting or recessed mounting by means of an outer casing



Calypto_1 | Movable spotlight | powerLED 1.5 W 500 mA**type**

Chrome	CRI 80	87059
Nickel	CRI 80	87060

colour

3000 K	178 lm	W
4000 K	190 lm	N
5000 K	216 lm	C
R - G - B - Y on request		

optic

10°	10
30°	30



99195
ON/OFF
1 - 2 art.




99115
1-10V
1 - 12 art.



99114
DALI
1 - 12 art.



84349
Outer casing

Calypto_2 | Movable spotlight | powerLED 1.5 W 500 mA**type**

Chrome	CRI 80	87067
Nickel	CRI 80	87068

colour

3000 K	178 lm	W
4000 K	190 lm	N
5000 K	216 lm	C
R - G - B - Y on request		

optic

30°	30
50°	50
70°	70



99195
ON/OFF
1 - 2 art.



99115
1-10V
1 - 12 art.



99114
DALI
1 - 12 art.



84349
Outer casing

