




OH!



491

619

IN





707

Diffusore in polietilene.
Rosone in metallo verniciato texturizzato bianco.

Polyethylene diffuser.
Ceiling rose in white textured painted metal.

Oh!_P65 LED


topLED CRI 90 | 350 mA | 6 W DC



Opt | 3000K 836 lmS - 625 lmD
DI | 15111

Oh!_P65 LED


topLED CRI 90 | 350 mA | 7 W DC



Opt | 3000K 1022 lmS - 845 lmD
DI | 16113

Oh!_P65 LED


topLED CRI 90 | 220-240 V
13 W DC - 15 W AC



Opt | 3000K 1930 lmS - 1584 lmD
DI | 16106

Oh!_P65 LED


topLED CRI 90 | 220-240 V
18 W DC - 20 W AC



Opt | 3000K 2748 lmS - 2115 lmD
DI | 16110

Oh!_P65 LED

topLED CRI 90 | 220-240 V
26 W DC - 27 W AC



Opt | 3000K 3835 lmS - 2856 lmD
DI | 16115

Electronics

Oh!_P65 LED 6W - Oh!_P65 LED 7W
KIT0066 ON/OFF Driver (1-2 art.)

Finishes ☐ Natural Polyethylene


Fox Belysning AB Tellusgången 8 Telefonplan 126 26 Hägersten 08-440 85 40

519





OH!



491

619

IN




707

Diffusore in polietilene.
Rosone in metallo verniciato texturizzato bianco.

Polyethylene diffuser.
Ceiling rose in white textured painted metal.



Oh!_P65 E27
220-240 V




2,5m

E27 1 x 30 W Max Halogen
(LED/FLUORESCENT bulbs
compatible)

16180

Oh!_P65 E27
220-240 V




2,5m

E27 1 x 46 W Max Halogen
(LED/FLUORESCENT bulbs
compatible)

16168

Oh!_P65 E27
220-240 V




2,5m

E27 1 x 46 W Max Halogen
(LED/FLUORESCENT bulbs
compatible)

16169

Oh!_P65 E27
220-240 V



2,5m

E27 1 x 57 W Max Halogen
(LED/FLUORESCENT bulbs
compatible)

16170

Finishes ☐ Natural Polyethylene