



A must for the finest outdoor accent lighting, JADE 9, a rounded compact spotlight featuring in-built electronics and power supply unit, creates visual interest to specific architectural features or details, boosting their peculiarity with differently shaped optics outputs.



TECHNICAL SPECIFICATIONS

9 high brightness RGB power LEDs unit Continuously variable light intensity DMX, automatic and Master-Slave mode Infrared remote control Power supply: standard 100÷240V / 50-60Hz Power consumption: 0.2A @ 230V / 23W max EASY EDITION standard 100÷277V / 50-60Hz Power consumption: 0.11A @ 230V / 25W max Electrical class: I Meets CE and CSA safety standards Aluminium body

IP66
Operating temperature:
-40°C to 50°C (-40°F to 122°F)
Integrated electronic thermal
protection management **Easy Edition**, for budget restraint projects where
DMX, colour changing, and dimming options are
not specified, available on request.
2.2 Kg
EASY EDITION 2 Kg

DIGITAL CONTROL SYSTEM SPECIFICATIONS AND CONFIGURATIONS AVAILABLE ON OUR WEBSITE





CODES

AL3440/60 JADE 9 CW/WW SPOT AL3420 JADE 9 RGB SPOT AL3442/62 JADE 9 CW/WWNARROW AL3422 JADE 9 RGB NARROW AL3444/64 JADE 9 CW/WW MEDIUM AL3424 JADE 9 RGB MEDIUM AL3446/66 JADE 9 CW/WW WIDE AL3426 JADE 9 RGB WIDE AL3448/68 JADE 9 CW/WW EXTRA WIDE AL3428 JADE 9 RGB EXTRA WIDE AL3450/70 JADE 9 CW/WW ELLIPTICAL AL3430 JADE 9 RGB ELLIPTICAL AL3452/72 JADE 9 CW/WW ELLIPTICAL WIDE AL3432 JADE 9 RGB ELLIPTICAL WIDE

AL4354 JADE 9 EASY

NOTES

Jade 9 must always be purchased with AL1321 Infrared Remote Control. More Jade 9 units can be controlled with one AL1321. On request, Jade 9 is available also in the CSA certified version.

All code extensions of the EASY EDITION can be found on our website.

ACCESSORIES





AL1321 INFRARED REMOTE CONTROL





FEATURES AND OPTIONS









BEAM ANGLE REFERENCE

SPOT NARROW 11° 21° MEDIUM WIDE 41° EXTRA WIDE 68° **ELLIPTICAL** 9°x41° ELLIPTICAL WIDE 30°x38°

PHOTOMETRIC DETAILS AVAILABLE ON OUR WEBSITE







