

# archiline



Archiline is a linear outdoor light offering a high level of luminosity and flexibility. This extremely wide and competitive range is the result of many years' research. Each item is precision engineered using top-quality materials, and each Archiline family offers a range of outputs, with dedicated narrow, wide, elliptical and asymmetric wallwasher beams and optical compartments designed to ensure a uniquely pure beam, easyplug connectors for simpler installation, various dimmer protocols, a choice of monochrome warm and natural white or RGBW, with the colours being mixed in the optic.

#### **Recessed model materials**


Anodised 6060 aluminium alloy or AISI 316L stainless steel flange

Extra-clear tempered glass or white ceramic varnished tempered glass diffuser

#### **Wall/ceiling model materials**

Anodised 6060 aluminium alloy or AISI 316L stainless steel body

Extra-clear tempered glass diffuser




3,6 W DC - 4,5 W AC CRI80

<b>Anod. Bk.</b>	<b>92138</b>	3000K	483 lm	<b>W</b>	General	<b>00</b>
		4000K	504 lm	<b>N</b>		

Installation accessories



**98724**  
Outer casing




6 W DC - 7,3 W AC CRI80

<b>Anod. Bk.</b>	<b>92139</b>	3000K	828 lm	<b>W</b>	General	<b>00</b>
		4000K	864 lm	<b>N</b>		

Installation accessories



**98725**  
Outer casing



12 W DC - 14,3 W AC

<b>Anod. Bk.</b>	<b>92142</b>	3000K	1656 lm	<b>W</b>	General	<b>00</b>
		4000K	1728 lm	<b>N</b>		

Installation accessories




**98726**  
Outer casing

Cables On/Off

<b>99057</b>	<b>98147</b>	<b>98146</b>
2 m power supply cable F 3 pin	5 m extension M+F 3 pin	10 m extension M+F 3 pin

Archiline\_FL RGBW DMX | Linear profiles | 190-250V | topLED 25 W/m




8,4 W DC - 10 W AC CRI80

Anod. Bk.	<b>92143</b>	RGBW natural white	<b>Q</b>	General	<b>00</b>
		RGBW warm white	<b>V</b>		

Installation accessories



**98724**  
Outer casing




13,6 W DC - 16 W AC CRI80

Anod. Bk.	<b>92144</b>	RGBW natural white	<b>Q</b>	General	<b>00</b>
		RGBW warm white	<b>V</b>		

Installation accessories



**98725**  
Outer casing



24 W DC - 25 W AC CRI80



Anod. Bk.	<b>92145</b>	RGBW natural white	<b>Q</b>	General	<b>00</b>
		RGBW warm white	<b>V</b>		


Installation accessories



**98726**  
Outer casing

Electronics

  
DMX controllers  
 995

  
**99385**  
DMX/RDM  
address

  
Splitter ALLinONE  
Start & Continuity  
 1008

  
**98986**  
DMX LINE  
Clouser 120 Ohm

Cables power+DMX

<b>98662</b> 1 m extension all in one power + DMX M+F 6 pin shield	<b>98663</b> 5 m extension all in one power + DMX M+F 6 pin shield
--	--