

envelope





A versatile and aesthetically minimal applique resembling a small envelope. Coming with single (fit for indoor installation), double or quadruple emission, Envelope allows to obtain light effects capable of lighting and furnishing all at once.

Materials

Aluminium body

Envelope_1 | Path-marker | powerLED 1 W 350 mA



Efficiency - CRI 80

White	96976	2700 K	136 lm	M	180°	18
Grey	96978	3000 K	145 lm	W		
Cor-Ten	96979	4000 K	155 lm	N		

Electronics



89419 ON/OFF 1 - 2 art.	89421 ON/OFF 3 - 6 art.	99183 ON/OFF 6 - 12 art.



IP66

1009 Recessed casing
84336 / 84915

Envelope_2 | Path-marker | powerLED 1 W 350 mA



Efficiency - CRI 80

White	96971	2700 K	136 lm	M	180°	18
Grey	96973	3000 K	145 lm	W		
Cor-Ten	96974	4000 K	155 lm	N		



Electronics

		+ driver CV 24V		+ driver CV 24V
89144 ON/OFF 1 - 2 art.	99708 0/1-10V converter 1 - 4 art.		99711 DALI converter 1 - 4 art.	



1009 Recessed casing
84336 / 84915

Envelope_4 | Path-marker | powerLED 1 W 350 mA



Efficiency - CRI 80

White	96966	2700 K	136 lm	M	180°	18
Grey	96968	3000 K	145 lm	W		
Cor-Ten	96969	4000 K	155 lm	N		

Electronics

		+ driver CV 24V		+ driver CV 24V
89144 ON/OFF 1 - 2 art.	99708 0/1-10V converter 1 - 4 art.		99711 DALI converter 1 - 4 art.	



1009 Recessed casing
84336 / 84915