

HIGH PROTECTION

Body in polycarbonate with UV protection.
Plugs in anodised 6026 aluminium.
Neoprene cables.

High
Protection
Embossed
(EB)



Construction details

Polycarbonate tube with waterproof closing system using rotating side plugs in 6026 anodised aluminium. Special TCS® valve as protective air vent to prevent the formation of condensation inside the tube, thereby ensuring long life for the lamp. Quick connector system with a range of accessory cables to create continuous lines directly connected to the electrical mains, thanks to the driver included in each bar. LED tube featuring light source made up of latest generation high density SMD Top LEDs mounted on PCB. In the case of embossed internal diffuser with the use of optics in the 30, 12, perfect cleaning of the cone of light is ensured thanks to the special embossing.

High
Protection
Wired

High
Protection



Cable exit positions

The orthogonal cable exit from the High Protection tube allows the space between two continuous tubes to be minimised, thereby optimising the continuous line of light effect. The High Protection Wired version has a linear cable exit position along the axis of the tube, through the closing plug.




Connection examples (High Protection)

Single connection

Multiple connection

Max 600W ON/OFF
Max 300W DALI




Insulating
terminal plug.



PROTON THERAPY CENTER
Trento (Italy)



High Protection | topLED | 220-240 V AC | 13 W DC - 14,5 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94679	W	1440 - 1102	30 (99°x 85°)
DALI - CRI 90	N	1501 - 1148	12 (107°x 129°)
EB 84402			

Accessories (pag 619-620)



High Protection | topLED | 220-240 V AC | 20 W DC - 22 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94680	W	2318 - 1960	30 (126°x 106°)
DALI - CRI 90	N	2478 - 2096	12 (128°x 125°)
EB 84405			

Accessories (pag 619-620)


High Protection | topLED | 220-240 V AC



	Cct	Im S - Im D	Im S - Im D	Opt
CRI 90				
37W DC - 40,5W AC	W	3974 - 3491	2479 - 2181	30 (137°x 95°)
EB 94681	N	4248 - 3732	2699 - 2375	12 (143°x 118°)
DALI - CRI 90				
20W DC - 22W AC				
EB 84408				

Accessories (pag 619-620)


High Protection Wired | topLED | 220-240 V AC | 13 W DC - 14,5 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 95465	W	1440 - 1102	30 (99°x 85°)
DALI - CRI 90	N	1501 - 1148	12 (107°x 129°)
EB 84411			

Accessories (pag 619-620)


High Protection Wired | topLED | 220-240 V AC | 20 W DC - 22 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 95466	W	2318 - 1960	30 (126°x 106°)
DALI - CRI 90	N	2478 - 2096	12 (128°x 125°)
EB 84414			

Accessories (pag 619-620)

High Protection Wired | topLED | 220-240 V AC



	Cct	Im S - Im D	Im S - Im D	Opt
CRI 90				
37W DC - 40,5W AC	W	3974 - 3491	2479 - On req	30 (137°x 95°)
EB 95467	N	4248 - 3732	2699 - On req	12 (143°x 118°)
DALI - CRI 90				
20W DC - 22W AC				
EB 84417				

Accessories (pag 619-620)

Linear systems

618

Finishes	Cct
EB Embossed	W 3000
	N 4000

Accessories



99225

IP66 ON-OFF connection box.

83229

IP66 DALI connection box.

suitable for: High Protection / High Protection Wired



99216

1500 mm

1500 mm long power cable with female quick connector in IP66 (ON-OFF / DALI).

suitable for: High Protection



99217

150 mm

Extension cable with male/female quick connector in IP66 for direct connection between tubes (ON-OFF / DALI).

suitable for: High Protection



99218

1500 mm

Extension cable with male/female quick connector in IP66 for direct connection between tubes (ON-OFF / DALI).

suitable for: High Protection



99229

per meter

Extension cable in neoprene 2x1 mm² ON-OFF.
Example: 99229 x 3 pz = 3 m.

83213

per meter

Extension cable in neoprene 4x1 mm² DALI.
Example: 83213 x 3 pz = 3 m.

83205

per meter

Extension cable in neoprene 4x1,5 mm² DALI.
Example: 83205 x 3 pz = 3 m.

suitable for: High Protection Wired



98729


Quick connector IP68 socket/plug.
2 poles ON-OFF.

99768

Quick connector IP68 socket/plug.
5 poles DALI.

suitable for: High Protection Wired


Accessories



99219

Suspension fixing system with anodised aluminium ring, tightening safety screws, 1200 mm long steel cable, adjustment system for the cable and fixing with screws and anchors. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired



C-F100017

Suspension fixing system with 1200 mm long steel cable, adjustment system for the cable and fixing with screws and anchors. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired



99221

Male/female fittings in anodised aluminium to join articles, fixing screws and tightening safety screws. To be used only with the suspension fixing kit (code 99219 - indicated above).


suitable for: High Protection



99222

Surface installation system with screw locking and fixing using self-tapping screw and anchor. Made in transparent polycarbonate. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired



99220

Clip fixing spring in nickel plated steel, self-tapping screw, anchor and o-ring for safety closing. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired



99238

Clip fixing spring in transparent polycarbonate, self-tapping screw, anchor and o-ring for safety closing. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired



99224

Corner installation system with pair of side brackets with screw locking and fixing using self-tapping screws and anchors.

suitable for: High Protection



99223

Installation system with pair of side brackets with screw locking and fixing using self-tapping screws and anchors.

suitable for: High Protection




PARKHAUS ZECHE ZOLLVEREIN

Essen (Germany)

Design and construction supervision:
Dreßler Bau GmbH, Essem Herr Pauli

Lighting Design:
Engineer Büro Paulus Essen, Herr Gräf

Photography:
Linea Light GmbH



RESIDENCE CIVICO 3.9
Treviso (Italy)

Project:
Studio Architetti Associati
Giampietro & Stefano Cinel

Commissioned by:
Fralma Srl

Photography:
TheStudio

