

HIGH WIRED

Body in 6060 aluminium.
Diffuser in polycarbonate.

Construction details

Profile in 6060 anodised aluminium with cover in embossed. In the version with IP44 protection grade, the insulating cable gland is built in, absent in the IP40 version.



Surface installation

High Wired can be surface installed on the desired surface or on busbar, using specific fixing accessories.




Surface installation on busbar



Surface installation





High Wired | topLED | 220-240 V AC | 13 W DC - 14,5 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94908	W	1440 - 1141	30 (101°x 90°)
DALI - CRI 90	N	1501 - 1216	12 (111°x 112°)
EB 84382			

Accessories (pag 243)



High Wired | topLED | 220-240 V AC | 20 W DC - 22 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94909	W	2318 - 1883	30 (101°x 90°)
DALI - CRI 90	N	2478 - 2005	12 (111°x 122°)
EB 84385			

Accessories (pag 243)


High Wired | topLED | 220-240 V AC



	Cct	Im S - Im D	Im S - Im D	Opt
CRI 90		37W	20W	
37W DC - 40,5W AC	W	3974 - 3195	2479 - 1985	30 (101°x 90°)
EB 94910	N	4248 - 3403	2699 - 2159	12 (111°x 112°)
DALI - CRI 90				
20W DC - 22W AC				
EB 84388				

Accessories (pag 243)



High Wired IP44 | topLED | 220-240 V AC | 13 W DC - 14,5 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94911	W	1440 - 1141	30 (101°x 90°)
DALI - CRI 90	N	1501 - 1216	12 (111°x 112°)
EB 84393			

Accessories (pag 243)


High Wired IP44 | topLED | 220-240 V AC | 20 W DC - 22 W AC



	Cct	Im S - Im D	Opt
CRI 90			
EB 94912	W	2318 - 1883	30 (101°x 90°)
DALI - CRI 90	N	2478 - 2005	12 (111°x 122°)
EB 84396			

Accessories (pag 243)

High Wired IP44 | topLED | 220-240 V AC



	Cct	Im S - Im D	Im S - Im D	Opt
CRI 90		37W	20W	
37W DC - 40,5W AC	W	3974 - 3195	2479 - 1985	30 (101°x 90°)
EB 94913	N	4248 - 3403	2699 - 2159	12 (111°x 112°)
DALI - CRI 90				
20W DC - 22W AC				
EB 84399				

Accessories (pag 243)

Ceiling / Wall / Suspensions

242

Finishes	Cct
EB Embossed	W 3000
	N 4000

Accessories

1x



99226

Fastening kit with steel clips.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44

1x



99228

Fastening kit with safety clasp.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44



99229

per meter

Extension cable in neoprene 2x1 mm² ON-OFF.
Example: 99229 x 3 pz = 3 m.

83213

per meter

Extension cable in neoprene 4x1 mm² DALI.
Example: 83213 x 3 pz = 3 m.

suitable for: High Wired / High Wired IP44

1x



99227

Fastening kit with steel clips and connector.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44



99225

IP66 ON-OFF connection box.

suitable for: High Wired / High Wired IP44



98729

Quick connector IP68 socket/plug.
2 poles ON-OFF.

99768

Quick connector IP68 socket/plug.
5 poles DALI.

suitable for: High Wired / High Wired IP44

