

lafina




A light line just 7 millimetres thick. The ultra-slim light cuts that come with Lafina thanks to its small dimensions befit the walls and the ceiling. It comes with the frameless version, with plasterboard-installation option due to the special recessed casing, or exposed flange.

Materials

Aluminium body

Opaline polycarbonate diffuser







CRI 80 - 1,7 W

Anod. AL. **97379**

3000 K	135 lm	W	General	00
4000 K	140 lm	N		
2700 K	145 lm	M		

Electronics

**99374**
ON/OFF
1 - 44 art.**99332**
0/1-10V
1 - 88 art.**99722**
DALI
1 - 70 art.


Cables

**98449**
1 end cap
+ screws




CRI 80 - 3,3 W

Anod. AL. **97380**

3000 K	270 lm	W	General	00
4000 K	280 lm	N		
2700 K	290 lm	M		



Electronics

**99374**
ON/OFF
1 - 22 art.**99332**
0/1-10V
1 - 44 art.**99722**
DALI
1 - 36 art.


Cables

**98449**
1 end cap
+ screws




CRI 80 - 6,6 W

Anod. AL. **97381**

3000 K	540 lm	W	General	00
4000 K	560 lm	N		
2700 K	580 lm	M		




Electronics

**99374**
ON/OFF
1 - 11 art.**99332**
0/1-10V
1 - 22 art.**99722**
DALI
1 - 18 art.

Cables

**98449**
1 end cap
+ screws


Lafina_F | Linear profiles | 24 V | topLED




CRI 80 - 1,7 W

Anod. AL	96617	3000 K	135 lm	W	General	00
		4000 K	140 lm	N		
		2700 K	145 lm	M		


Electronics



99374
ON/OFF
1 - 44 art.



99332
0/1-10V
1 - 88 art.



99722
DALI
1 - 70 art.

Accessories




Cables




98445
Recessed casing

CRI 80 - 3,3 W


Anod. AL	96618	3000 K	270 lm	W	General	00
		4000 K	280 lm	N		
		2700 K	290 lm	M		




Electronics



99374
ON/OFF
1 - 22 art.



99332
0/1-10V
1 - 44 art.



99722
DALI
1 - 36 art.

Accessories




Cables




98446
Recessed casing

CRI 80 - 6,6 W


Anod. AL	96619	3000 K	540 lm	W	General	00
		4000 K	560 lm	N		
		2700 K	580 lm	M		




Electronics



99374
ON/OFF
1 - 11 art.



99332
0/1-10V
1 - 22 art.



99722
DALI
1 - 18 art.

Accessories





Cables



98447
Recessed casing

Lafina_F | Outer-casings



type suitable for

Anod. AL	96617	250 mm	98445
Anod. AL	96618	500 mm	98446
Anod. AL	96619	1000 mm	98447

Aluminium profile for trimless installation; recessed cardboard ceiling mounting.