


narcissus

Materials

AISI 316L stainless steel body
Extra-clear tempered glass diffuser




Narcissus | Accent lighting | 198-264 V AC | powerLED 2 W DC - 2,2 W AC



	Cct	lm S - D	Optic
Steel 95151	M 2700	219 - 0n req	08 N.Spot (10°)
	W 3000	233 - 178	15 Spot (18°)
	N 4000	249 - 189	30 Flood (27°)
			60 W.Flood (45°)

Accessories Pag. 807


Narcissus | Accent lighting | 198-264 V AC | powerLED 6 W DC - 8 W AC



	Cct	lm S - D	Optic
Steel 95152	M 2700	536 - 476	15 Spot (18°)
	W 3000	566 - 503	30 Flood (27°)
	N 4000	626 - 556	60 W.Flood (45°)

Accessories Pag. 807

Narcissus | Accent lighting | 198-264 V AC | arrayLED 13 W DC - 13,5 W AC



	Cct	lm S - D	Optic
Steel 81945	M 2700	1724 - 0n req	15 Spot -
	W 3000	1724 - 0n req	30 Flood -
	N 4000	1854 - 0n req	60 W.Flood -

Accessories Pag. 807

Accessories



	description
84890	Steel peg 250 mm
suitable for: Narcissus	



	description
98112	Steel peg 700 mm
suitable for: Narcissus	