

nitum





A recessed spotlight that allows to create true dot-like light reticules, Nitum frees your creativity. The wide range of optics and colour temperatures allows unrivalled project versatility, enhanced by the recessed casing accessory for integration with plasterboard surfaces.

Materials

Brass or steel body



Nitum_R | Decorative spotlight | powerLED 1 W 350 mA



Efficiency - CRI 80


White	88421	2700 K	136 lm	M	Spot	10
Chrome	85043	3000 K	145 lm	W	Medium Flood	30
Nickel	85044	4000 K	155 lm	N	Flood	50
Steel	86881	5000 K	165 lm	C	Flood	70
					Wide Flood	12
					General	00




1009 Recessed casing
84915 / 84336

RTG 88421W30 85044W50
85043W30
85044W10
85044W30
85044W00

Electronics




89144
ON/OFF
1 - 2 art.



99708
0/1-10V converter
1 - 4 art.

+ driver CV 24V
▶ 981





99711
DALI converter
1 - 4 art.

+ driver CV 24V
▶ 981



Nitum_R | Decorative spotlight | powerLED 2 W 630 mA



Efficiency - CRI 80


White	88423	2700 K	219 lm	M	Spot	10
Chrome	85059	3000 K	233 lm	W	Medium Flood	30
Nickel	85060	4000 K	249 lm	N	Flood	50
Steel	86883	5000 K	266 lm	C	Flood	70
					Wide Flood	12
					General	00




1009 Recessed casing
84901

RTG 88423W10 85059W50
85423W30 85060W30
85423W50 85060W50
85423W00
85423N30

Electronics




89147
ON/OFF
1 - 2 art.



99710
0/1-10V converter
1 art.

+ driver CV 24V
▶ 981





99713
DALI converter
1 art.

+ driver CV 24V
▶ 981



Nitum_R | Decorative spotlight | powerLED 2,1 W 220 mA



Efficiency - CRI 80

White	88568	RGB	Z	Spot	10
Chrome	86612			Medium Flood	30
Nickel	86613			Flood	60
Steel	86674			General	00




1009 Recessed casing
84901

RTG 86612Z60

Electronics



RF driver CC
▶ 972



DMX driver CC
▶ 977



DMX controllers
▶ 995





driver CV 24V/48V
▶ 981-982



switching CV 24V/48V
▶ 986-989

Nitum_Q | Decorative spotlight | powerLED 1 W 350 mA



Efficiency - CRI 80


White	88422	2700 K	136 lm	M	Spot	10
Chrome	85045	3000 K	145 lm	W	Medium Flood	30
Nickel	85046	4000 K	155 lm	N	Flood	50
Steel	86882	5000 K	165 lm	C	Flood	70
					Wide Flood	12
					General	00




1009 Recessed casing
84915 / 84336

RTG 88422W30

Electronics




89144
ON/OFF
1 - 2 art.



99708
0/1-10V converter
1 - 4 art.



+ driver CV 24V
▶ 981



99711
DALI converter
1 - 4 art.

+ driver CV 24V
▶ 981

Nitum_Q | Decorative spotlight | powerLED 2 W 630 mA



Efficiency - CRI 80


White	88424	2700 K	219 lm	M	Spot	10
Chrome	85061	3000 K	233 lm	W	Medium Flood	30
Nickel	85062	4000 K	249 lm	N	Flood	50
Steel	86884	5000 K	266 lm	C	Flood	70
					Wide Flood	12
					General	00




1009 Recessed casing
84901

RTG 88424W30
88424W50
85061W30
85062W30

Electronics




89147
ON/OFF
1 - 2 art.



99710
0/1-10V converter
1 art.



+ driver CV 24V
▶ 981



99713
DALI converter
1 art.

+ driver CV 24V
▶ 981

Nitum_Q | Decorative spotlight | powerLED 2,1 W 220 mA




Efficiency - CRI 80

White	88569	RGB	Z	Medium Flood	30
Chrome	86614			Flood	60
Nickel	86615			General	00
Steel	86675				




1009 Recessed casing
84901

Electronics



RF driver CC
▶ 972



DMX driver CC
▶ 977



DMX controllers
▶ 995



driver CV 24V/48V
▶ 981-982



switching CV 24V/48V
▶ 986-989