

sub



AquaStop®


This underwater point light features IP68 and AquaStop® protection and an ultrathin 9-millimetre flange. When positioned in series, it can be used to create attractive dot patterns to highlight the bottom of a pool or architectural feature in contact with water.

Materials

Brass body



Sub_R | Underwater luminaires | powerLED 1.5 W 500 mA



RTG 97315W15
97315W30
97315W60
97315W00
97315N30

CRI 80

Steel	97315	2700 K	187 lm	M	Spot	15
		3000 K	199 lm	W	Medium Flood	30
		4000 K	213 lm	N	Flood	60
					General	00

Electronics



89422
ON/OFF
1 - 2 art.



89423
ON/OFF
2 - 3 art.




99181
ON/OFF
3 - 6 art.



99185
ON/OFF
6 - 12 art.

Sub_Q | Underwater luminaires | powerLED 1.5 W 500 mA



CRI 80

Steel	97317	2700 K	187 lm	M	Spot	15
		3000 K	199 lm	W	Medium Flood	30
		4000 K	213 lm	N	Flood	60
					General	00

Electronics



89422
ON/OFF
1 - 2 art.



89423
ON/OFF
2 - 3 art.



99181
ON/OFF
3 - 6 art.



99185
ON/OFF
6 - 12 art.

