

Vos

F.O.L.™



Fire Rating®



Tiling



The families of Vos downlights are characterized by an **optical unit consisting of a reflector with F.O.L.™ filtering system**. The fixed and tilting versions, with the exception of the asymmetric version, feature a **pinhole controlled-reflectance optical compartment** with a recessed light source fitted with anti-glare screen.


Passive heat dissipation
Die cast aluminium heat sink

Light management
Black-coated aluminium casing and optical compartment

Minimalist sturdiness
Thin yet resistant steel flange with embossed finish



Vos_R | Downlight | powerLED 8 W 630 mA



type

White	CRI 80	95510
Black	CRI 80	95511

colour

2700 K	639 lm	M
3000 K	674 lm	W
4000 K	745 lm	N

optic

15°	15
30°	30
60°	60



99129

ON/OFF
1 art.


99115

1-10V
1 - 2 art.

99114

DALI
1 - 2 art.

Vos_R | Downlight | powerLED 15 W 400 mA



type

White	CRI 95	95524
Black	CRI 95	95525

colour

2700 K	1070 lm	M
3000 K	1160 lm	W

optic

15°	15
30°	30
45°	45



White	CRI 80	95512
Black	CRI 80	95513

2700 K	1446 lm	M
3000 K	1560 lm	W
4000 K	1670 lm	N

15°	15
30°	30
45°	45

99113

ON/OFF
1 art.


99116

1-10V
1 art.

99131

DALI
1 art.

Vos_R | Downlight | arrayLED 25 W 720 mA



type

White	CRI 95	95548
Black	CRI 95	95549

colour

2700 K	2347 lm	M
3000 K	2511 lm	W
4000 K	2695 lm	N

optic

15°	15
30°	30
45°	45



White	CRI 80	95536
Black	CRI 80	95537

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N

15°	15
30°	30
45°	45

99112

ON/OFF
1 art.


99188

1-10V, DALI
1 art.

99330

DALI
1 art.

Vos_RJ | Downlight | powerLED 8 W 630 mA



type

White	CRI 80	95824
Black	CRI 80	95825

colour


2700 K	639 lm	M
3000 K	674 lm	W
4000 K	745 lm	N

optic

15°	15
30°	30
60°	60

**99129**ON/OFF
1 art.**99115**1-10V
1 - 2 art.**99114**DALI
1 - 2 art.

Vos_RJ | Downlight | powerLED 15 W 400 mA



type

White	CRI 80	95865
Black	CRI 80	95866

colour



2700 K	1446 lm	M
3000 K	1560 lm	W
4000 K	1670 lm	N

optic

15°	15
30°	30
45°	45

**99113**ON/OFF
1 art.**99116**1-10V
1 art.**99131**DALI
1 art.

Vos_RJ | Downlight | arrayLED 25 W 720 mA



type

White	CRI 95	96285
Black	CRI 95	96286

colour


2700 K	2347 lm	M
3000 K	2511 lm	W
4000 K	2695 lm	N

optic

15°	15
30°	30

**99112**ON/OFF
1 art.**99188**1-10V, DALI
1 art.**99330**DALI
1 art.

Vos_Q | Downlight | powerLED 8 W 630 mA



type

White	CRI 80	95560
Black	CRI 80	95561

colour


2700 K	639 lm	M
3000 K	674 lm	W
4000 K	745 lm	N

optic

15°	15
30°	30
60°	60

**99129**ON/OFF
1 art.**99115**1-10V
1 - 2 art.**99114**DALI
1 - 2 art.

Vos_Q | Downlight | powerLED 15 W 400 mA



type

White	CRI 95	95574
Black	CRI 95	95575

colour

2700 K	1070 lm	M
3000 K	1160 lm	W
45°		45

optic

15°	15
30°	30
45°	45


White	CRI 80	95562
Black	CRI 80	95563

2700 K	1446 lm	M
3000 K	1560 lm	W
4000 K	1670 lm	N
45°		45

15°	15
30°	30
45°	45

**99113**ON/OFF
1 art.**99116**1-10V
1 art.**99131**DALI
1 art.

Vos_Q | Downlight | arrayLED 25 W 720 mA



type

White	CRI 95	95598
Black	CRI 95	95599

colour

2700 K	2347 lm	M
3000 K	2511 lm	W
4000 K	2695 lm	N

optic

15°	15
30°	30
45°	45



White	CRI 80	95586
Black	CRI 80	95587

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N
45°		45

15°	15
30°	30
45°	45

**99112**ON/OFF
1 art.**99188**1-10V, DALI
1 art.**99330**DALI
1 art.

Vos_QY | Downlight | arrayLED 25 W 720 mA



type

White	CRI 80	95857
Black	CRI 80	95858

colour

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N

optic

Asym.	07
-------	-----------


**99112**ON/OFF
1 art.**99188**1-10V, DALI
1 art.**99330**DALI
1 art.

"Messe" - Düsseldorf (Germany)

Installed in the ceiling in the reception area of the Messe Düsseldorf GmbH, Vos_Q ensures a pure, well-defined asymmetric light beam with a controlled wall projection. The light illuminates the entrance walls in an effective yet discreet way.



Vos_QJ | Downlight | powerLED 8 W 630 mA



type

White	CRI 80	95826
Black	CRI 80	95827

colour

2700 K	639 lm	M
3000 K	674 lm	W
4000 K	745 lm	N

optic

15°	15
30°	30
60°	60



99129

ON/OFF
1 art.


99115

1-10V
1 - 2 art.

99114

DALI
1 - 2 art.

Vos_QJ | Downlight | powerLED 15 W 400 mA



type

White	CRI 80	95956
Black	CRI 80	95957

colour

2700 K	1446 lm	M
3000 K	1560 lm	W
4000 K	1670 lm	N

optic

15°	15
30°	30
45°	45



99113

ON/OFF
1 art.



99116

1-10V
1 art.

99131

DALI
1 art.

Vos_QJ | Downlight | arrayLED 25 W 720 mA



type

White	CRI 95	96287
Black	CRI 95	96288

colour

2700 K	2347 lm	M
3000 K	2511 lm	W
4000 K	2695 lm	N

optic

15°	15
30°	30

White	CRI 80	95960
Black	CRI 80	95961

2700 K	3101 lm	M
3000 K	3321 lm	W
4000 K	3568 lm	N

15°	15
30°	30



99112

ON/OFF
1 art.

99188

1-10V, DALI
1 art.

99330

DALI
1 art.

