



Warp_QY | Downlight | powerLED 2 W 630 mA



Balance - CRI 92

White	90822	2700 K	157 lm	M	Spot	15
Black	90823	3000 K	179 lm	W	Medium Flood	30
					Flood	60



White	90826
Black	90827

Efficiency - CRI 80

White	90820	2700 K	219 lm	M	Spot	15
Black	90821	3000 K	233 lm	W	Medium Flood	30
		4000 K	249 lm	N	Flood	60




White	90824
Black	90825




The power supply requires a larger hole than the one indicated for the spotlight

Electronics




89147
ON/OFF
1 - 2 art.



99710
0/1-10V converter
1 art.

+ driver CV 24V
981




99713
DALI converter
1 art.

+ driver CV 24V
981



Warp_QY | Downlight | powerLED 4 W 350 mA



Balance - CRI 92

White	90838	2700 K	395 lm	M	Spot	15
Black	90839	3000 K	423 lm	W	Medium Flood	30
		4000 K	456 lm	N	Flood	60



White	90842
Black	90843

Efficiency - CRI 80

White	90836	2700 K	490 lm	M	Spot	15
Black	90837	3000 K	490 lm	W	Medium Flood	30
		4000 K	529 lm	N	Flood	60




White	90840
Black	90841




The power supply requires a larger hole than the one indicated for the spotlight

Electronics




89145
ON/OFF
1 art.



99708
0/1-10V converter
1 art.

+ driver CV 24V
981





99711
DALI converter
1 art.

+ driver CV 24V
981



Warp_QY | Downlight | powerLED 10 W 800 mA



HC

Balance - CRI 92

White	90854	2700 K	960 lm	M	Spot	15
Black	90855	3000 K	1034 lm	W	Medium Flood	30
		4000 K	1108 lm	N	Flood	60

White	90858
Black	90859

Efficiency - CRI 80

White	90852	2700 K	1108 lm	M	Spot	15
Black	90853	3000 K	1194 lm	W	Medium Flood	30
		4000 K	1280 lm	N	Flood	60

White	90856
Black	90857

HC

Electronics



99735
ON/OFF
1 art.





99733
0/1-10V
1 art.



99731
DALI
1 art.

Warp_QY | Downlight | arrayLED 15 W 400 mA



HC

Balance - CRI 92

White	90870	2700 K	1568 lm	M	Spot	15
Black	90871	3000 K	1677 lm	W	Medium Flood	30
		4000 K	1804 lm	N	Flood	60

White	90874
Black	90875

Efficiency - CRI 80

White	90868	2700 K	1932 lm	M	Spot	15
Black	90869	3000 K	1932 lm	W	Medium Flood	30
		4000 K	2078 lm	N	Flood	60


White	90872
Black	90873

HC


Electronics




99740
ON/OFF
1 art.



99739
0/1-10V
1 art.



99738
DALI
1 art.



HC

Balance - CRI 92


White	90886	2700 K	2598 lm	M	Spot	15
Black	90887	3000 K	2794 lm	W	Medium Flood	30
		4000 K	2990 lm	N	Flood	60
White	90890					
Black	90891					

Efficiency - CRI 80

White	90884	2700 K	3210 lm	M	Spot	15
Black	90885	3000 K	3431 lm	W	Medium Flood	30
		4000 K	3431 lm	N	Flood	60
White	90888					
Black	90889					

HC


Electronics



99112
ON/OFF
1 art.




99188
0/1-10V DALI
1 art.




99330
DALI
1 art.

90884W60




Photometric curve



Light beam



25 LUX 300 LUX 500 LUX 700 LUX 750 LUX 900 LUX 1000 LUX



Floor plan