


Nero Accent

LED 3000 K

Wall Recessed Luminaire, Floor Recessed Luminaire, Light distribution direct, asymmetric
Accent Washlights
Finish in Stainless Steel, Cover clear

Product EL97003-78-W
Operating Technology 83734
Note: The components must be ordered separately.

Light Technique

Colour rendering index CRI > 80
Colour temperature 3000 K
50.000 h lifetime (L70)
Asymmetrical version for step lighting
LED colour finish optional

Luminaire housing

Light proof housing made of die cast zinc
Surface satin stainless steel
Tempered safety glass, clear
Protection class IP 67
Max. load 500 kg

Operating and assembly technology

LED gear box to be separately
Round cut-outs also for square luminaires for an easy adjustement
Identical version for wall and floor luminaires
Suitable to assemble in raised floor and wall

Optional equipment

Concrete mounting box 88090R03
Mounting accessories 88015, 88005R03, 88018

Light Technique

Lamp Wattage	2 W
Colour Rendering Index	80
Colour Temperature	3000 K
Beam spread angle γ	asymmetric
Luminaire Luminous Flux	43 Lm
System Efficiency	22 Lm/W
Energy Efficiency Class	A
Number Luminaires LZ	4.51

Operating technology

Connector	screw connector, 2 x 0.75 mm ²
Operation Mode	standard, IP67

Dimensions

Reflector Size	Q03
Length L	60 mm
Width W	60 mm
Cut-out CO	51 mm
Installation Depth RD	45 mm
Total Weight	0.4 kg

The information contained in our datasheets is based on current and relevant information at the time of original issue or publication.
We constantly strive to improve and upgrade our products from a performance, materials and quality perspective.
This may result in a difference between actual product performance and that shown on data sheets, warranties are based on actual delivered product performance.

